



Adhesive, Sealant, & Lubricant Dispensing Solutions

Coating Application:

Machine data

- Working width: adjustable from ..... mm to .....mm
- Centric: [ ] yes, ..... or .....
- Speed: from .....m/min to .....m/min ( Max 150'/min.)

To be coated material

- Name / material: .....
[ ] Sample attached [ ] datasheet attached
- Thickness /structure: .....mm / ..... stock
- Surface treated: [ ] No [ ]Yes .....
- Is sensitive to: Temperatur: .....
Tension: .....
Injury of surface: .....
Others: .....
- Form of the material: [ ]Endless Coil Diameter.....mm Coil Length.....M
[ ] Sheet Dimension: Length .....mm X Width .....mm

Glue and application data

- Type of glue: [ ] EVA [ ] PA/Polyamid [ ]PS/Pressure Sensitive
[ ] PUR [ ] TPU [ ] Others .....
- Supplier: ..... [ ] Datasheet attached via fax.
- Product-no.: .....
- Viscosity, in mPas / cPs: .....°C: .....cps. ....°C: .....cps. ....
°C: .....cps. ....
- Form of Application: [ ]Continuous [ ] Intermittent
[ ] Full surface [ ] Stripes
- Coating weight: min.: .....g/m² max.: .....g/m²
- Limit of tolerance: + .....% - .....%
- Glue consumption: min.: .....kg/h max.: .....kg/h
- Instant delivery pump rate: max.: .....kg/h
- Special requests: .....

Final product

- Use: .....

General information

- Adress of customer: .....